

THE DFG 200 is a compact, single-head diamond floor grinder

The DFG 200 has been developed as an introductory model to the SPE DFG Floor Grinder range. Simple to operate and available in single phase electric, the DFG 200 meets the requirements of rental companies and flooring contractors. The operator's handle height is fully adjustable and the machine fits easily into the trunk of a car for transportation. The machine can be fitted with a wide selection of diamond, polymer, and PCD attachments, providing a versatile solution for smaller surface preparation projects.



Features

- Robust construction
- 50mm (2") dust extraction port
- Dust-free when used with suitable SPE dust control vacuum
- Large diameter wheels for excellent mobility and stability
- Removable weight to vary grinding pressure
- Simple adjustment to level to the floor surface
- Adjustable dust skirt

Applications

- Accurate grinding of concrete surfaces
- Removal of old floor coatings and contaminants
- Latex and adhesive removal
- Grinding and polishing of resin-based and tiled terrazzo
- Remedial work to rain and frost damaged slabs



Specifications		
Type	DFG 200 110V	DFG 200 220V
Part Number	DFG 200-5	DFG 200-3
Power Output	3hp/2.2kW	3hp/2.2kW
Voltage	110V	220V
Cycles	50/60hz	50/60hz
Head Speed	1400rpm	1400rpm
Motor Speed	1400rpm	1400rpm
Machine Dimensions		
Length	880mm (34.6")	880mm (34.6")
Width	370mm (14.6")	370mm (14.6")
Height	700mm (27.6")	700mm (27.6")
Weight	49kg (108lbs)	49kg (108lbs)
Removable Weight	5.5kg (12lbs)	5.5kg (12lbs)

UK & Europe Electrical Requirements (Plug and cable sizes available for other countries, please enquire for details)

Machine	Voltage	Plug Size	Cable Size	Max Cable Length	Transformer	Generator
DFG 200-5	110V	32A 3 Pin	4mm 3 Core	30m (98')	5 kVA	8 kVA
DFG 200-3	230V	16A 4 Pin	2.5mm 3 Core	100m (98')	-	8 kVA