



Developed to mix promptly and effectively, quantities of a wide range of materials. The mixer is driven by a sealed motor and gearbox providing many years of trouble-free operation. An optional perforated paddle is available to increase agitation by forcing material through its perforations. The machine is both robust and portable, offering the user high output and single handed operation.

### Features

- Disposable mixing container
- Sealed for life gearbox and motor
- Robust monocoque steel chassis
- Light and portable
- Quickly disassembles for transportation in a van or car
- Fully protected against overload

### Mixing Applications

- Epoxy Screed
- Repair mortars
- Cement
- Adhesives
- Polyester Resin
- Liquid Plastics
- Bituminous Sealants
- Paints and Powders

Specifications			
Type	1 Phase		3 Phase
Part Number	MIX 25-1	MIX 25-2	MIX 25-3
Power Output	1hp/0.75kW	1hp/0.75kW	1hp/0.75kW
Voltage	110V	230V	400/460V
RPM	58	58	58
Capacity	32L (8.5 US gal)	32L (8.5 US gal)	32L (8.5 US gal)
Machine Dimensions			
Length	700mm (27.6")	700mm (27.6")	700mm (27.6")
Width	460mm (18.1")	460mm (18.1")	460mm (18.1")
Height	813mm (32")	813mm (32")	813mm (32")
Weight	43kg (95lbs)	43kg (95lbs)	43kg (95lbs)

### UK & Europe Electrical Requirements (Plug and cable sizes available for other countries, please enquire for details)

Machine	Voltage	Plug Size	Cable Size	Max Cable Length	Transformer	Generator
MIX 25-1	110V	16A 3 Pin	2.5mm 3 Core	30m (98')	3 kVA	5 kVA
MIX 25-2	230V	16A 3 Pin	2.5mm 3 Core	30m (98')	-	5 kVA
MIX 25-3	400V	16A 5 Pin	2.5mm 4 Core	75m (246')	-	5 kVA